



TYPE	A	B
LED B/L	13.5	9.0

PIN	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18
NAME	DB7	DB6	DB5	DB4	DB3	DB2	DB1	DB0	E1	R/W	RS	V0	VSS	VCC	E2	NC	LED+	LED-

SPECIFICATIONS	
1.	DISPLAY TYPE: STN/TRANSFLECTIVE/POSITIVE/Y-G
2.	LCD DRIVING VOLTAGE: 4.4V
3.	LOGIC VOLTAGE: 5.0V
4.	VIEWING DIRECTION: 6 O'CLOCK
5.	OPERATING TEMP: -0° C~50° C
6.	STORAGE TEMP: -20° C~70° C
7.	DRIVE MODE: 1/16 DUTY, 1/5 BIAS
8.	BACKLIGHT: YELLOW GREEN/BOTTOMBACKLIGHT/5.0V
9.	CONTROL/DRIVE IC: SPLC780D-001B-C/SPLC100A2-C
10.	OTHER:
MECHANICAL TOL. ± 0.3 UNLESS SPECIFIED	

NOTE:

DESCRIPTION:		C/D	
SCALE: FIT			
SHEET: 1 OF 1			
	PROJECTION	MODEL	SERIAL NUMBER
UNIT:	mm	TC4004A-01A	
APP:		CHK:	DWN:
DATE:		DATE:	