



Electrical :
 Rated voltage: 300V
 Rated current: 12A
 Contact resistance: 20mΩ
 Insulation resistance: 500MΩ/500V
 Withstanding Voltage: AC2000V/1Min
 Wire range: 22-14AWG 1.5mm²

Material
 Housing: PA66,UL 94V-0
 Cage: Brass,Nickel Plated
 Screws: M2.5 steel Zinc plated
 Wire guard: phosphor bronze Nickel Plated

Mechanical
 Temp. Range: -40° C ~ +105° C
 MAX Soldering: +250° C for 5 Sec.
 Torque: 0.4Nm (3.5lb.in)
 Strip length: 6mm

Order Information

L-KLS2-331K-5.00-XXP- 3 S
 Screw: Slot Screw
 Color: Black
 Number of Pole: 02 ~ 24P

GENERAL TOLERANCE	ANGLE TOLERANCE	PROJECTION	Description:
X. ±0.60	X. ±5°	UNITS	
.X ±0.38	.X ±3°	SHEET SIZE	
.XX ±0.25	.XX ±2°	KLS P/N:	KLS2-331K-5.00-XXP-3S

Draw by: Date	
Check by:: Date	
SCALE	SHEET OF

KLS ELECTRONIC CO., LTD.