



**Material**  
**Housing:** PA66, UL 94V-0  
**Screw:** M2 Steel, Zn plated  
**Clamp:** Brass, Ni plated  
**Cage:** Brass, Ni plated

**Electrical**  
**Rated voltage:** 300V  
**Rated current:** 8A  
**Contact Resistance:** 20 mΩ  
**Insulation resistance:** 500MΩ/DC500V  
**Withstand voltage:** AC2000V / 1 min  
**Wire Range:** 28 ~ 16AWG 1.5mm<sup>2</sup>

**Mechanical**  
**Temp. Range:** -40 °C ~ +105 °C  
**Strip length:** 6 ~ 7mm  
**Torque:** 0.2Nm(1.77Lbin)

**Order Information**

**L-KLS2-EDGF-3.81-XXP-4S00**

RoHS  
Terminal Block  
Pitch  
No.: of Pole  
Color: 4- Green  
Screw: S-Slot Screw C-Cross Screw  
Product Code: 00 ~ 99

GENERAL TOLERANCE		ANGLE TOLERANCE		Description:	
X. ±0.60		X. ±5°		Pluggable Terminal block 3.81MM	
.X ±0.38		.X ±3°		KLS P/N:	KLS2-EDGF-3.81-XXP-4S-00
.XX ±0.25		.XX ±2°			
Draw by	2015-09-01	PROJECTION		NingBo KLS ELECTRONIC CO.,L TD.	
Check by	2015-09-15	UNITS	mm		
SCALE		SHEET SIZE	A4		