



Material
 Housing: PA66, UL 94V-0
 Clamp: Brass, Ni plated
 Pin Header: Brass, Tin plated
 Screw: M3.0, steel Zinc plated

Electrical
 Rated voltage: 300V
 Rated current: 20A
 Contact Resistance: 20 mΩ
 Insulation resistance: 500MΩ/DC500V
 Withstand voltage: AC2000V / 1 min
 Wire Range: 26~12AWG 2.5mm²

Mechanical
 Temp. Range: -40 °C ~ +105 °C
 Strip length: 6~7mm
 Torque: 0.5Nm (4.5Lb.in)

Order Information

L-KLS2-129R-7.50-XXP-4 S 00
 RoHS
 Terminal Block
 Pitch
 No.: of Pole
 Color: 4- Green
 Screw: S-Slot Screw
 Product Code: 00~99

GENERAL TOLERANCE	ANGLE TOLERANCE	Description:		
X. ±0.60	X. ±5°	Screw CONN TERM Block 7.50mm		
.X ±0.38	.X ±3°	KLS P/N:	KLS2-129R-7.50-XXP-4S	
.XX ±0.25	.XX ±2°			
Draw by 2015-09-01	PROJECTION		NingBo KLS ELECTRONIC CO.,L TD.	
Check by 2015-09-15	UNITS			mm
SCALE	SHEET SIZE			A4