

Material
 Housing: PA66, UL94V-0
 Screws: M2.0, Steel, Zn plated
 Clamp: Phosphor bronze, Ni Plated
 Cage: Brass, Zn plated
 Slide block: Steel, Zn plated



Electrical
 Rated voltage: 300V
 Rated current: 8A
 Contact Resistance: 20 mΩ
 Insulation resistance: 500MΩ/DC500V
 Withstand voltage: AC2000V / 1 min
 Wire Range: 28 ~ 16AWG 1.5mm²

Mechanical
 Temp. Range: -40 °C ~ +105 °C
 Strip length: 7mm
 Torque: 0.2Nm(1.8 bin)

Order Information

L-KLS2- EDKCM -3.81-XXP-4 S 00

RoHS
 Terminal Block
 Pitch
 No. of Pole
 Color: 4- Green
 Screw: S-Slot Screw C-Cross Screw
 Product Code: 00 ~ 99

GENERAL TOLERANCE	ANGLE TOLERANCE	Description:	
X. ±0.60	X. ±5°	Pluggable Terminal Block 3.81MM	
.X ±0.38	.X ±3°	KLS P/N:	KLS2-EDKCM-3.81-XXP-4S-00
.XX ±0.25	.XX ±2°	 NingBo KLS ELECTRONIC CO.,L TD.	
Draw by 2015-09-01	PROJECTION 		
Check by 2015-09-15	UNITS mm		
SCALE	SHEET SIZE A4		