

- C1:VCC
- C2:RST
- C3:CLK
- C4:Reserved
- C5:GND
- C6:VPP
- C7:I/O
- C8:Reserved


SIM CARD BOTTOM VIEW

Material:

Housing:Hi-Temperature Plastic,UL 94V-0.Black.
 Terminal:Copper Alloy.Gold Flash Plated On All Terminal,AND 50u" Min Nickel Underplated On All over.
 Shell:Stainless Steel.50u" Nickel Underplated On All over,Gold Flash On Solder PAD.

Electrical:

Current Rating:0.5 A.
 Voltage Rating:5.0 vrms.
 Insulation Resistance:1000MΩ Min.At DC500V DC.
 Withstanding Voltage:250V AC RMS For 1 Minute.
 Contact Resistance:100mΩ Max.At 10mA/20mV max.
 Operating Temperature:-40°C TO +85°C.
 Mating Cycles:5000 Insertions.



| GENERAL TOLERANCE | | ANGLE TOLERANCE | | PROJECTION | Description: |
|-------------------|--|-----------------|--|------------|-------------------|
| X. ±0.15 | | X. ±5° | | UNITS | mm |
| .X ±0.03 | | .X ±3° | | SHEET SIZE | A4 |
| .XX ±0.05 | | .XX ±2° | | KLS P/N: | L-KLS1-SIM-033-8P |

| | | | |
|-----------|-------|-------|------------|
| Draw by: | Jenny | Date: | 2018-03-10 |
| Check by: | | Date: | 2018-03-10 |
| SCALE | | SHEET | 1 OF 1 |



NingBo KLS ELECTRONIC CO.,L TD.

Double SIM CARD CONN,
 PUSH PULL 8P×2,H3.0mm,SMD