



H	PATR NO.
1.40	L-KLS1-SIM-045-1.4
2.00	L-KLS1-SIM-045-2.0
2.50	L-KLS1-SIM-045-2.5
3.00	L-KLS1-SIM-045-3.0
3.40	L-KLS1-SIM-045-3.4
4.20	L-KLS1-SIM-045-4.2
4.70	L-KLS1-SIM-045-4.7

Material:
Housing: LCP(NY 9T), UL 94V-0.
Contact: Selective Gold Flash.

Electrical:
Voltage Current Rating: 1A 50V AC
Insulation Resistance: 1000M Ω Min.
Contact Withstanding Voltage: AC500V For 1 Minute.
Temperature Rating: -40°C TO +85°C

GENERAL TOLERANCE	ANGLE TOLERANCE	PROJECTION		Smart Card CONN, SMD 8P, with Right CD Pin L-KLS1-SIM-045-XX
X. ± 0.15	X. $\pm 5^\circ$	UNITS	mm	
.X ± 0.03	.X $\pm 3^\circ$	SHEET SIZE	A4	
.XX ± 0.05	.XX $\pm 2^\circ$	KLS P/N:		L-KLS1-SIM-045-XX
Draw by: Jenny	Date: 2018-03-10	NingBo KLS ELECTRONIC CO.,L.TD.		
Check by:	Date: 2018-03-10			
SCALE	SHEET 1 OF 1			