



**Material:**

Material: Phosphor Bronze (C5191-H).

Housing: LCP (NY 9T), UL 94 V-0.

Contact: Selective Gold Flash.

**Electrical:**

Voltage Current Rating: 1A 50V AC

Insulation Resistance: 1000M $\Omega$  Min.

Contact Withstanding Voltage: AC500V For 1 Minute.

Temperature Rating: -40°C TO +85°C

H	PATR NO.
1.40	L-KLS1-SIM-045A-1.4
2.00	L-KLS1-SIM-045A-2.0
2.50	L-KLS1-SIM-045A-2.5
3.00	L-KLS1-SIM-045A-3.0
3.40	L-KLS1-SIM-045A-3.4
4.20	L-KLS1-SIM-045A-4.2
4.70	L-KLS1-SIM-045A-4.7

GENERAL TOLERANCE	ANGLE TOLERANCE	PROJECTION	
X. $\pm 0.15$	X. $\pm 5^\circ$	UNITS	mm
.X $\pm 0.03$	.X $\pm 3^\circ$	SHEET SIZE	A4
.XX $\pm 0.05$	.XX $\pm 2^\circ$	KLS P/N:	
Draw by: Jenny	Date: 2018-03-10		
Check by:	Date: 2018-03-10		
SCALE	SHEET 1 OF 1		

Smart Card CONN, SMD  
8P, with LEFT CD Pin

L-KLS1-SIM-045A



NingBo KLS ELECTRONIC CO., L.TD.