



Material

Housing:Hing Temperature Thermoplastic
with g.f,UL 94 V-0.

Contact:Copper Alloy,t=0.20mm.

Shell:SUS,t=0.20mm.

Electrical:

Current Rating:1A Max.

Dielectric Withstanding Voltage:
100 V AC for 1 min.

Contact Resistance:50m Ω Max.

Insulation Resistance:100M Ω Min.

Total Mating Force:3.57 kgf Max.

Total Unmating Force:1.0 kgf Min.

Temperature Range: -30°C Up To +80°C

| | | | |
|-------------------|------------|------------|---|
| GENERAL TOLERANCE | PROJECTION | | Description: |
| .X ± 0.50 | UNITS | mm | CONN PLUG MICRO USB TYPE B CLIP L8.8 |
| .X ± 0.25 | SCALE | 1:1 | |
| .XX ± 0.10 | Draw by: | Jenny | KLS P/N: L-KLS1-236-5M7-B |
| ANGLE TOLERANCE | Check by: | | NingBo KLS ELECTRONIC CO.,L TD. |
| .X $\pm 5^\circ$ | Date | 2018-03-01 | |
| .X $\pm 3^\circ$ | SHEET | 1 OF 1 | |
| .XX $\pm 2^\circ$ | | | |