



Unnoted tolerance						
Size	A	B	C	⌀	E	F
0-6	0.03	0.05	0.08	0.10	0.15	0.20
6-18	0.05	0.08	0.10	0.15	0.20	0.25
18-30	0.08	0.10	0.15	0.20	0.25	0.35
30-50	0.10	0.15	0.20	0.25	0.35	0.50
50-80	0.15	0.20	0.25	0.35	0.50	0.65
80-120	0.20	0.25	0.35	0.50	0.65	0.80
120-180	0.25	0.35	0.50	0.65	0.80	0.95
180-250	0.35	0.50	0.65	0.80	0.95	1.15

Specifications	Figure	Colour	Specifications	Figure	Colour
FAK001Z-A		Black	FAK001Z-G		Gray
FAK001Z-B		White	FAK001Z-H		Pink
FAK001Z-C		Blue	FAK001Z-I		Beige
FAK001Z-C		Purple	FAK001Z-K		Yellow
FAK001Z-E		Green	FAK001Z-Z		Sky blue
FAK001Z-F		Brown			

Technical requirements:

1. There are no adverse phenomena such as shrinkage, pike, oil stain, glue shortage and miscellaneous color on the surface of the product.
2. The product conforms to ROHS environmental protection standard.

Material:

Shell: PA66 +GF15,UL94V-0

Buckle: PA66 +GF15,UL94V-0

Electrical Specifications

Impedance: 50 Ω

Frequency Range: DC-4 GHz

Voltage Rating: 335 volts

VSWR: 1.3 Max. Dielectric

Withstanding Voltage: 1000 volts rms

Insulation Resistance: 4000 MΩ Min.

Temperature Range: -40°C to +85°C

PROJECTION		Description:
UNITS	mm	Fakra connectors
SCALE	1:1	
Draw by:	Jenny	KLS P/N: L-KLS1-FAK001Z
Check by:		NingBo KLS ELECTRONIC CO.,L TD.
Date	2019-02-20	
SHEET	3 OF 1	