



PCB Layout Tolerance: ±0.05

■ STAND OFF AREA

SPECIFICATION
 Rated Load: DC 20V 7A
 Contact resistance: 30mΩ, max
 Insulation resistance: 100MΩ, min
 Withstand Voltage: AC500V
 Actuating Force: 3-20N
 Life: 5000 cycles
 Operating Temperature: -30°C - 70°C

NO.	Description	QTY	Material	Plating
1	Housing	1	LCP	---
2	Spring Piece	1	Bronze	Sn-Plating
3	Curve Piece	1	Brass	Sn-Plating
4	PIN	1	Zinc Alloy	Au-Plating
5	Coat	1	Bronze	Ni-Plating
6	PEG	1	SUS301	Ni-Plating



GENERAL TOLERANCE	PROJECTION	Symbol	Description:
X. ±0.50	UNITS	mm	20V 7A DC Jack Mid Mount 3.20mm
.X ±0.25	SCALE	1:1	
.XX ±0.10	Draw by:	Jenny	
ANGLE TOLERANCE	Check by:		KLS P/N: L-KLS1-MDC-036
X. ±5°	Date	2019-03-01	 NingBo KLS ELECTRONIC CO.,L TD.
.X ±3°	SHEET	1 OF 1	
.XX ±2°			