


PIN	φ1.65	φ2.0	φ2.35	φ2.5
APPD				

SCHMATIC



SPECIFICATION

Rated Load:DC 30V 0.5A
 Contact resistance:30mΩ, max
 Insulation resistance:100MΩ, min
 Withstand Voltage:AC500V
 Actuating Force:3-20N
 Life:5000 cycles
 Operating Temperature:-30°C-70°C

NO.	Description	QTY	Material	Plating
1	Housing	1	PBT/PA66	---
2	Flat Piece	1	H62 Brass	Cu-Sn-Plating
3	Spring	1	65Mn Steel	Cu-Sn-Plating
4	PIN Foot	1	H59 Brass	Ni-Plating
5	Contact	1	Brass	Cu-Sn-Plating
6	Cover	1	PF	---

GENERAL TOLERANCE	PROJECTION		Description:
X. ±0.50	UNITS	mm	DC POWER Jack DIP
.X ±0.25	SCALE	1:1	
.XX ±0.10	Draw by:	Jenny	KLS P/N: L-KLS1-DC-012B
ANGLE TOLERANCE	Check by:		NingBo KLS ELECTRONIC CO.,L TD.
X. ±5°	Date	2019-03-01	
.X ±3° .XX ±2°	SHEET	1 OF 1	