


Pin Hole Layout Jack Bottom View



PIN	φ2.0	φ2.5.
APPD		

SPECIFICATION
 Rated Load:DC 30V 1A
 Contact resistance:30mΩ, max
 Insulation resistance:100MΩ, min
 Withstand Voltage:AC500V
 Actuating Force:3-20N
 Life:5000 cycles
 Operating Temperature:-30°C-70°C

NO.	Description	QTY	Material	Plating
1	PIN Terminal	1	0.4T Brass	Silver Plated
2	Sleeve Spring	1	0.25T Phosphor Bronze	Silver Plated
3	Break Terminal	1	0.4T Brass	Silver Plated
4	Pin(φ2.0)	1	Copper	Ni-Plating
5	Housing	1	PA9T	Black Color
6	Cover	1	PA9T	Black Color

GENERAL TOLERANCE	PROJECTION		Description:
X. ±0.50	UNITS	mm	DC POWER Jack SMT HORIZONTAL
.X ±0.25	SCALE	1:1	
.XX ±0.10	Draw by:	Jenny	
ANGLE TOLERANCE	Check by:		KLS P/N: L-KLS1-TDC-006
X. ±5°	Date	2019-03-01	NingBo KLS ELECTRONIC CO.,L TD.
.X ±3°	SHEET	1 OF 1	
.XX ±2°			