



Pins	A	B	C	D
06	7.6	7.62	10.1	12.26
08	10.1	7.62	10.1	12.26
10	12.6	7.62	10.1	12.26
12	15.2	7.62	10.1	12.26
14	17.7	7.62	10.1	12.26
16	20.3	7.62	10.1	12.26
18	22.8	7.62	10.1	12.26
20	25.3	7.62	10.1	12.26
22	27.8	7.62	10.1	12.26
24	30.4	7.62	10.1	12.26
28	35.5	7.62	10.1	12.26

24	30.5	15.24	17.7	19.88
28	35.5	15.24	17.7	19.88
32	40.6	15.24	17.7	19.88
36	45.7	15.24	17.7	19.88
40	50.8	15.24	17.7	19.88
42	53.3	15.24	17.7	19.88
48	60.9	15.24	17.7	19.88

Material:

Housing: PBT UL 94V~0

Contacts: Beryllium copper or Phosphor Bronze
Plating: Au 2u" or Sn over 50u" nickel

Electrical Characteristics:

Current Rating: 3.0 AMP

Insulator Resistance: 1000MΩ min.

Contact Resistance: 20mΩ max.

Operating Temperature: -40°C ~ +105°C

Order Information:

L-KLS1-217T-XX-Z-1

L: RoHS

IC Socket

XX-No. of 06 ~ 48pin

Material:

Y-Imported Beryllium copper

Z-Domestic Phosphor Bronze

B Size: 1=7.62mm 3=15.24mm

GENERAL TOLERANCE	PROJECTION		Description:
.X ±0.50	UNITS	mm	2.54mm Pitch IC Socket Connector SMT Type
.X ±0.25	SCALE	1:1	
.XX ±0.10	Draw by:	Jenny	
ANGLE TOLERANCE	Check by:		KLS P/N: L-KLS1-217T-XX-Z-1
.X ±5°	Date	2018-03-01	NingBo KLS ELECTRONIC CO.,L TD.
.X ±3°	SHEET	1 OF 1	
.XX ±2°			