



**Material**  
Housing: PA66, UL94V-0  
Contactor: Copper alloy  
Contactive Coating: Sn plated

**Electrical**  
Rated voltage: 600V  
Rated current: 40A  
Withstand voltage: AC2000V / 1 min  
Wire Range: 8 ~ 24AWG

**Mechanical :**  
Pitch/Poles: 7.50/01~18  
Temp. Range: -40 °C ~ + 105 °C  
Strip length: 15mm  
Pin Dimensions: 1.7x0.8  
PCB Hole Dimensions:  $\phi 2.1$

**Order Information**  
L-KLS2-262V-7.50-XXP-4

RoHS  
Terminal Block  
Pitch  
No.: of Pole  
Color: 4- Green

GENERAL TOLERANCE		ANGLE TOLERANCE		Description:					
X. $\pm 0.60$	.X $\pm 0.38$	.XX $\pm 0.25$	X. $\pm 5^\circ$	.X $\pm 3^\circ$	.XX $\pm 2^\circ$				
Draw by 2022-04-06				PROJECTION	 <b>NingBo KLS ELECTRONIC CO.,L TD.</b>				
Check by 2022-04-06				UNITS					
SCALE				SHEET SIZE					
									
				mm					
				A4					
				<table border="1"> <tr> <td>KLS P/N:</td> <td>L-KLS2-262V-7.50-XXP-4</td> </tr> <tr> <td colspan="2" style="text-align: center;">Pluggable Terminal Block 7.50 MM</td> </tr> </table>		KLS P/N:	L-KLS2-262V-7.50-XXP-4	Pluggable Terminal Block 7.50 MM	
KLS P/N:	L-KLS2-262V-7.50-XXP-4								
Pluggable Terminal Block 7.50 MM									