




1
RoHS Compliance



Material:
Insulation: PA66+GF, UL 94 V-0
Connector Pin: Brass, 0.025u" Gold plated
Nut/Screw: Brass, Nickel plating

Electrical Characteristics:
Rated current: 03Pin 4A, 06Pin 08Pin 1.5A
Rated voltage: 03~06Pin 60V, 08Pin 30V
Contact Resistance: 10mΩ Max

Mechanical properties:
IP rating: IP67
Wire gauge: 20~26AWG / 0.14~0.50mm²
Mechanical characteristics: mating/cycle > 100 cycle
Operating Temperature: -40°C ~ +85°C



L-KLS15-M8A-L103



L-KLS15-M8A-L104



L-KLS15-M8A-L106



L-KLS15-M8A-L108

Order Information:

L-KLS15-M8A-L108

L: RoHS

Screw type: M8

A: A-Coding

Type: _____

L1: Soldering, Panel mount,

Front lock, Female

Number of Contacts: _____

(03P 04P 06P 08P)

ANGLE TOLERANCE	PROJECTION	Description:	IP67 M8 A-coding Soldering Female, Panel mount, Front lock
±3°			
GENERAL TOLERANCE	UNITS	mm	KLS P/N: L-KLS15-M8A-L108
x.x ±0.30	SHEET SIZE	A4	
x.xx ±0.20	Draw:	Daniel	2022-04-01
x.xxx ±0.10	Check:	Daniel	2022-04-01



NingBo KLS ELECTRONIC CO.,LTD.